



GULLIVER

FOR GREAT PERFORMANCES

Automation
for industrial
sliding gates



- Product in conformity with European standards.
- Electromechanical automation, 230v a.c., 400v a.c. and 24v d.c.
- Suitable for gates from 1000 kg to 2200 kg.
- Suitable for intensive, industrial and collective operation.
- Easy to install, thanks to the adjustable fixing plate.
- Motor control by encoder (in the models in 230V ac and 400V ac) which adjusts the speed while keeping the couple during the slowdown.
- Slow-down and reverser on obstacle.
- Integrated limit-switch.
- Simple unlocking system by key.
- Electromechanical brake to get a more immediate stop of the gate.
- Internal ventilation to get a more intensive duty.
- Grease soaked gear motor.

GULLIVER is the automation for sliding gates from 1000 kg to 2200 kg, where an intensive duty is required. The sturdiness and the choice of the details are a guarantee of reliability in time. Thanks to the electronic clutch, safety is assured. The control board is integrated in the case, aiding the already quick installation of the Gulliver.



LIVI

STURDY & RELIABLE, WITH MANY YEARS OF EXPERIENCE

Electromechanical
operator for
sliding gates



- Product in conformity with European standards.
- Electromechanical automation, 230V a.c. and 24V d.c.
- Suitable for gates up to 900 kg.
- Easy to install, thanks to the adjustable fixing plate.
- Motor control by encoder (in 230V a.c. models) which adjusts the speed while keeping the couple during the slowdown.
- Integrated limit switches.
- Simple unlocking system by key.
- Electronic force adjustment.
- Grease soaked gear motor.

LIVI is the operator for sliding gates up to 900 kg, which combines a great sturdiness and reliability with an agreeable and original design, which has been marking out this product for several years. Thanks to the mechanical or electronic clutch, safety is assured. The control board is integrated in the case, aiding the already quick installation of the Livi and allowing rapid, precise & stable programming.



LIVI

STURDY & RELIABLE, WITH MANY YEARS OF EXPERIENCE



THE MODELS

Operators 230V a.c.

6RR: operator with built-in control board art. 203RR*, for gates up to 600 kg, motor control by encoder, with built-in limit switches.

9RR: operator with built-in control board art. 203RR*, for gates up to 900 kg, motor control by encoder, with built-in limit switches.

805RR: operator with built-in control board art. 203RR*, for gates up to 800 kg, motor control by encoder, not self locking, with built-in limit switches.

403E: operator with built-in control board art. 212E, for gates up to 400 kg, with built-in limit switches.

803E: operator with built-in control board art. 212E, for gates up to 800 kg, with built-in limit switches.

Operators 24V d.c.

5/24RR/F: operator with built-in control board art. 124RR*, for gates up to 500 kg, with built-in limit switches.

8/24RR/F: operator with built-in control board art. 124RR*, for gates up to 800 kg, with built-in limit switches.

**all control boards included in the RR range come equipped with a 2-channel wireless receiver 433 Mhz, pedestrian opening, electronic adjustment of speed and force, reverser function on obstacle and slow-down.
All functions are adjusted by 3 buttons and a digital display.*

DEA System control boards are planned to optimize the performances of Livi range.

TECHNICAL INFORMATION

Model	6RR 403E	9RR 803E	805RR	5/24RR/F	8/24RR/F
Motor power supply (V)	230 V a.c.	230 V a.c.	230 V a.c.	24 V d.c.	24 V d.c.
Capacity (W)	320	450	350	80	110
Duty cycle	30%	30%	30%	80%	80%
Max thrust (N)	340	490	275	210	260
Operating temperature (°C)	-20°÷40°	-20°÷40°	-20°÷40°	-20°÷40°	-20°÷40°
Speed (m/min)	10	10	10,8	10	10
Protection level	IPX4	IPX4	IPX4	IPX4	IPX4
Weight with packing (Kg)	11	12,5	12,5	12	12

ACCESSORIES



Art. 111
Nylon rack, with metal interior and fixing screws.



Art. 112
Galvanized steel rack 22 x 22 mm.



Art. 113
Galvanized steel rack 30x12 mm with zinc-plated spacers.



Art. 460
Foundation plate to be cemented.



Art. 450
Unlocking device kit for LIVI. To be used in connection with BLINDOS.



Art. BLINDOS
Safety enclosure to place external unlocking device handle.



Art. Soft
Safety rubber profile (complete with aluminium base) useful to reduce the impact forces. To be used together with control boards of range RR.



Simple unlocking system by key



Metal body and highly sturdy components

DIMENSIONS

